

Lionbridge

Lionbridge App for Oracle Eloqua

Setup Guide

Version 1.5.5

August 25, 2017

Copyright

© Copyright 2017 Lionbridge Technologies, Inc. All rights reserved. Published in the USA. March, 2016.

Lionbridge and the Lionbridge logotype are registered trademarks or trademarks of Lionbridge Technologies, Inc. in the United States and other countries. All other trademarks used herein are the property of their respective owners. The opinions of third-party contributors remain theirs alone and do not necessarily represent the views of Lionbridge Technologies.

Contents

1 Welcome to the Lionbridge App for Oracle Eloqua	5
1.1 Terminology	5
1.2 About the Clay Tablet Translation Platform	7
1.3 How the Lionbridge App Works with Oracle Eloqua	7
1.4 Using this Guide	8
1.5 How to Contact Clay Tablet Support	9
2 Before You Set Up the Lionbridge App for Oracle Eloqua	12
3 Installing the Lionbridge App for Oracle Eloqua	13
4 Getting Started with CloudBroker	14
4.1 CloudBroker at a Glance	15
5 Configuring the Lionbridge App in CloudBroker	16
5.1 Configuring Clay Tablet Languages	16
5.2 Configuring Global Translation Settings	18
5.3 Configuring Lionbridge Freeway Authentication	20
5.4 Configuring SDL TMS Entries	22
5.5 Viewing and Testing Eloqua Authentication Settings	24
5.6 Configuring Translation Settings	26
5.7 Configuring Translation Settings for Eloqua Dynamic Content	30
5.8 Configuring Translation Providers	36
6 Configuring User Access	40
6.1 Managing Teams	43
6.1.1 Adding or Editing a Team	44
6.1.2 Deleting a Team	47
6.2 Managing Users	48
6.2.1 Importing Users	49
6.2.2 Editing a User	50
6.2.3 Adding a User	52
6.2.4 Deleting a User	55
7 Administrative Tasks	57
7.1 Viewing Lionbridge App Information and Usage Data	57
7.2 Viewing Job Data	59

8 Appendix: Clay Tablet Language Codes	61
9 Appendix: Eloqua Language Codes	70
Index	80

1 Welcome to the Lionbridge App for Oracle Eloqua

Welcome to the Lionbridge App for Oracle Eloqua (Lionbridge App). This application is an Oracle Eloqua plug-in. It enables you to automate sending and retrieving assets from Oracle Eloqua, which dramatically reduces the effort required to create, maintain, and publish Web content in multiple languages.

1.1 Terminology

Amazon AWS	Amazon Web Services. A suite of web application products developed and sold by Amazon.com. Clay Tablet uses various AWS offerings in order to leverage their infrastructure and build rich, dynamic solutions for its customers, specifically, the Clay Tablet Platform. For details, see http://aws.amazon.com .
Amazon S3	Amazon Simple Storage Service. For details, see: http://aws.amazon.com/s3/ . The Lionbridge App and the Clay Tablet Platform use Amazon S3 to provide temporary storage services for the content sent to and from translation.
Amazon SQS	Amazon Simple Queue Service. For details, see: http://aws.amazon.com/sqs/ . The Lionbridge App uses Amazon SQS to provide Message Queue Services.
Asset	A content item that you manage using Eloqua, for example, articles, product descriptions, advertisements, photos, and video clips. Assets are instances of asset types.
Asset type	An object that you use to create assets of that type. An asset type is represented by a content entry form, where the set of fields define the type of content you will provide. For example, an Article asset type may have fields "Headline," "Abstract," "Author," "Post Date," and "Body," which are the content that composes the article.
Clay Tablet (CTT)	Clay Tablet Technologies, a Lionbridge company, and the corporate entity that publishes the Lionbridge App for Oracle Eloqua (App), CloudBroker, and the Clay Tablet Platform.
Clay Tablet Platform	The hosted (IaaS) connectivity platform that receives and routes content from content providers to translation providers and back during implementation. Clay Tablet Technologies configures the Platform based on the number and nature of systems involved in your system architecture.
CloudBroker	Lionbridge's server application for hosting the Lionbridge App for Oracle Eloqua. As a SaaS (Software as a Service), Eloqua does not support installing the Lionbridge App or any other external applications on its server. Therefore, the Lionbridge App is hosted on the Lionbridge CloudBroker server.
Freeway	The name of the Lionbridge translation portal for submitting content to and retrieving content from the Lionbridge translation provider.

FTP Server	File Transfer Protocol (FTP) is a standard network protocol used to transfer files from one host to another host over a TCP-based network, such as the Internet. Translation providers may receive and send files for translation using an FTP server.
IaaS	Infrastructure as a Service. The Clay Tablet Platform is an IaaS, because it is a hosted platform.
Keys	<p>The Lionbridge App uses keys to establish a secure, discrete connection between the app instance and the Platform.</p> <p>Very important: Do not copy the CMS address keys to multiple Oracle Eloqua instances, because this is a violation of the Clay Tablet License Agreement. Using the same CMS address keys on multiple Oracle Eloqua instances will cause the Connector to behave unexpectedly, which can result in lost translation content, orphaned projects, and inaccurate translation status reports. Clay Tablet will support technical issues caused by duplicating or incorrectly installing CMS address keys only on a time and materials basis.</p>
Lionbridge	The publisher of the Freeway translation portal and a translation provider. Users connect to the Freeway translation portal to submit content to and retrieve content from the Lionbridge translation provider.
Lionbridge App for Oracle Eloqua (App)	The software that Clay Tablet Technologies has developed and provides, which plugs into your Eloqua environment to provide connectivity to CloudBroker and our hosted Platform. In this document it is referred to as the Lionbridge App. This is the software you set up as you work through this guide.
MT	Machine translation. The translation provider can be a machine translation service, such as Google Translate.
On-Premise Platform	A version of the Clay Tablet Platform that is hosted and managed by the Clay Tablet client, instead of hosted on AWS by Clay Tablet.
Producer	CMS or another content system that sends content or documents out for translation. In this case, this is Eloqua.
Provider	A provider of translation services. The delivery of assets to the provider may be via an FTP server or a TMS connector.
SDL TMS	SDL Translation Management System™ is a global information management application.
Site	A site is your company's implementation of the Lionbridge App for Oracle Eloqua.
Support Asset	Supporting documents and their metadata. Support assets are not translated by the translation provider, but they provide helpful context for the translator.

TMS	Translation management system that the translation provider uses.
------------	---

1.2 About the Clay Tablet Translation Platform

Clay Tablet’s translation connectivity platform is the easiest, most flexible way to integrate content systems, including content management systems (CMSs) and other content producers, with translation providers and translation technologies.

Clay Tablet Platform is the hosted (IaaS) connectivity platform that receives and routes content from content management systems to translation providers and back, including to Lionbridge via Freeway or onDemand. It is hosted on Amazon Web Services (AWS). During implementation, Clay Tablet Technologies configures the Platform for your translation solution, based on the translation providers or systems you use. The Clay Tablet Platform uses the following services on AWS:


- S3 (Amazon Simple Storage Service), which provides storage services for the content sent to and from translation.
- SQS (Amazon Simple Queue Service), which provides message queue services.

1.3 How the Lionbridge App Works with Oracle Eloqua

The Lionbridge App is an important part of the Clay Tablet translation solution.

The Lionbridge App is registered as an app within Oracle Eloqua. Its functionality is displayed to the users as part of Oracle Eloqua.

As a SaaS (Software as a Service), Oracle Eloqua does not support installing the Lionbridge App or any other external applications on its server. Therefore, the Lionbridge App is hosted on the Lionbridge CloudBroker server.



Your translation systems architecture might look like the configuration above. It may have additional content producers or translation providers, but the core concepts remain the same.

During implementation, Clay Tablet works with you and your translation providers to configure and test the other elements of your translation solution, which are the Clay Tablet Platform's connections to your translation providers' systems.

1.4 Using this Guide

Purpose of this guide

This guide describes everything you need to know to set up the Lionbridge App for Oracle Eloqua (Lionbridge App). It describes how to register the Lionbridge App in Oracle Eloqua, and how to set it up in CloudBroker.

Recommendation: Review the user guide to fully understand the powerful features of the Lionbridge App.

Who should use this guide

This guide is intended for Eloqua administrators or system integrators.

What your company setup should be

This document assumes that:

- Your company is already using Oracle Eloqua.
- Clay Tablet Technologies has set up CloudBroker for your company to use the Lionbridge App to send out content for translation from Oracle Eloqua.
- Clay Tablet Technologies has set up the Clay Tablet Platform to send content to your translation providers.

What you should already know

This document assumes that:

- You have a strong working knowledge of Oracle Eloqua and its features.
- You are familiar with your company's translation process and requirements.
- You have valid user credentials to log into Oracle Eloqua.
- You have valid user credentials to log into the AppCloud Developer section of Oracle Eloqua.
- You have valid user credentials to log into CloudBroker as a site administrator.

How to find out more about the Lionbridge App for Oracle Eloqua

For information on using the Lionbridge App for Oracle Eloqua to send and receive content for translation, read the *Lionbridge App for Oracle Eloqua User Guide*.

Documentation conventions

This guide uses the following conventions:

Convention	Description
Bold	Highlights screen elements such as buttons, menu items, and fields.

Convention	Description
Courier	Highlights input, file names, and paths.
<i>Italics</i>	Highlights terms for emphasis, variables, or document titles.
>	Indicates a menu choice. For example, "Select Assets > Landing Pages. "

1.5 How to Contact Clay Tablet Support

Email @: support@clay-tablet.com

Telephone: +1-416-363-0888

You can submit a support ticket either:

- by email
- from the Clay Tablet Zendesk page, using your web browser

To submit a support ticket:

1. Do one of the following:

- Email support@clay-tablet.com, and cc (carbon copy) anyone to include in the ticket correspondence.

Important: Include the information and attachments in your email that are listed in the sub-sections below.

- Create a ticket in Zendesk:

- a. Open the Clay Tablet Zendesk page in your browser: <https://claytablet.zendesk.com>.
- b. Sign in to Zendesk. If you do not have sign-in credentials, see "[To view and update your support ticket in Zendesk:](#)" below.

Important: Include the information and attachments that are listed in the sub-sections below.

- c. Click **Submit a request**.
- d. In the **CCs** field, add anyone to include in the ticket correspondence.

Zendesk automatically creates a ticket and responds to everyone included in the cc field.

2. Everyone in the original cc receives updates unless they request to be removed from the ticket.

Important: Check your email spam folder (especially first-time Zendesk users) as sometimes email notifications from Zendesk are marked as spam.

When the issue is resolved, Clay Tablet closes the ticket.

Information to include in the support ticket:

- client name
- CMS or content system name and version
- Connector or App version installed
- name of job for which the issue occurs
- date of job submission
- detailed description of the issue
- any error text—copy and paste, if applicable

Files to attach to the support ticket:

- CMS log files for the date the issue occurred
- Clay Tablet log files for the date the issue occurred
- screen capture of the issue

To view and update your support ticket in Zendesk:

Important: You must log into Zendesk to view your support tickets there.

1. Open the Clay Tablet Zendesk page in your browser: <https://claytablet.zendesk.com>.
2. In the top-right corner, click **Sign in**, and enter your credentials.

Note: If you do not have sign-in credentials yet, then click either **Sign up** or **Get a password**, and follow the onscreen instructions.

Sign in to Clay Tablet Technologies

Email

Password

Stay signed in

Sign in

Your credentials will be sent over a secure connection

Cancel

I am an Agent

Forgot my password

New to Clay Tablet Technologies? [Sign up](#)

Have you emailed us? [Get a password](#)

If you've communicated with our support staff through email previously, you're already registered. You probably don't have a password yet, though.

3. After signing in, click **My activities** to view the tickets you opened or where you are cc'd.
4. To update tickets, you can reply or attach files.

For more information, refer to "Submitting and tracking support requests" in Zendesk's *Help Center guide for end-users*, at: <https://support.zendesk.com/hc/en-us/articles/203664386-Help-Center-guide-for-agents-and-end-users>.

Important: Zendesk refers to a *support ticket* as a *support request*. These terms are interchangeable.

2 Before You Set Up the Lionbridge App for Oracle Eloqua

Since Oracle Eloqua is a SaaS (software as a service) application, you install the Lionbridge App for Oracle Eloqua (Lionbridge App) in the Oracle Cloud Marketplace. The Lionbridge App is a plug-in on the Oracle Eloqua server.

After installing the Lionbridge App in the Oracle Cloud Marketplace, you configure it in CloudBroker, which is a SaaS for configuring and hosting apps that are plug-ins to SaaS content systems.

There are three main steps in setting up the Lionbridge App:

1. *As an Eloqua administrator*, you install the Lionbridge App from the Oracle Cloud Marketplace. For detailed instructions, see "[Installing the Lionbridge App for Oracle Eloqua](#)" on page 13.

Important: To install the Lionbridge App, you require the **Advanced Users - Marketing** permission or higher.

2. *As a Lionbridge CloudBroker site administrator*, you create a new site using the Eloqua plug-in and tie it to this Oracle Eloqua system. For detailed instructions, see "[Getting Started with CloudBroker](#)" on page 14 and "[Configuring the Lionbridge App in CloudBroker](#)" on page 16.
3. *As a Lionbridge CloudBroker site administrator*, you configure user access, including setting up teams and users. For detailed instructions, see "[Configuring User Access](#)" on page 40.

Once the setup is complete, Oracle Eloqua users can start using the Lionbridge App to manage translations.

3 Installing the Lionbridge App for Oracle Eloqua

You install the Lionbridge App for Oracle Eloqua in the Oracle Cloud Marketplace.

Important: To install the Lionbridge App, you require the **Advanced Users - Marketing** permission or higher.

To install the Lionbridge App:

1. Open the Oracle Cloud Marketplace: <https://cloud.oracle.com/marketplace/product/marketing>.
2. In the **Search** box at the top of the page, search for the Lionbridge App for Oracle Eloqua.
3. In the search results, click it.
4. In the top-right corner, click **Get App**.
5. If you are not already signed in to your Oracle account, then when prompted, sign in to this account.
6. Read the Oracle Cloud Marketplace Terms of Use, select the appropriate check boxes, and click **Next**.

Note: You must accept the terms of use to install the Lionbridge App.

The **Customer Details** dialog box opens.

7. Complete the required information and click **Submit**.


4 Getting Started with CloudBroker

You log into CloudBroker so that you can configure the Lionbridge App, which is its plug-in for Oracle Eloqua, for your site.



CloudBroker supports all browsers.

To access CloudBroker:

1. Open the CloudBroker login page in your Web browser:
<https://cb1-prod-na.ctt.lionbridge.com/CloudBroker/Login>.



2. Enter the *site administrator* credentials that Clay Tablet personnel provided, and click **Login**.
3. After logging in, you can:
 - ▶ change the password by clicking the dropdown menu for your username and selecting **Change password**.
 - ▶ change the language of the CloudBroker user interface by clicking the dropdown menu for **English** and selecting a different language.



Note: To log out of CloudBroker, click the dropdown menu for your username and select **Logout**.

4.1 CloudBroker at a Glance

After you log in to CloudBroker as a site administrator, you navigate using the **Site Administration** menu on the left.

The screenshot displays the CloudBroker Site Administration interface. At the top, the logos for Lionbridge, ORACLE, and eloqua are visible, along with a user profile and language selector. The left sidebar shows the 'Site Administration' menu with options like 'My Site', 'Site Providers', 'Site Teams', 'Site Users', 'Site Jobs', and 'My Translations'. The main content area is titled 'My Site' and contains a table of site information and a 'Statistics' table.

Active	Name	Platform	Lionbridge App	Content site name	Actions
1	My test	Public	Lionbridge App for Eloqua	TechnologyPartnerClayTabletTechnologies	Map Languages Configure Site

Total Jobs	Total Items	Total Items to LSP	Total Sent Out	Total Received	Total Completed	Total LocalTM	Total Providers	Total Site Teams	Total Site Users
35	522	512	512	512	522	754	1	2	14

Note: If you are an end user as well as a site administrator, then in the **Site Administration** menu, you can click **My Translations** to open the **Lionbridge App for Eloqua** menu. To return to the site administrator interface from there, in the **Lionbridge App for Eloqua** menu, click **Manage Site**.

5 Configuring the Lionbridge App in CloudBroker

A *site administrator* configures and manages the Lionbridge App's configuration in CloudBroker, which is a Clay Tablet SaaS for configuring apps that are plug-ins to SaaS content systems. The Lionbridge App for Oracle Eloqua is your *site*.

To configure the Lionbridge App in CloudBroker:

1. Log in to CloudBroker as a site administrator. For details, see ["Getting Started with CloudBroker"](#) on page 14.
2. Perform the following configuration tasks:
 - ["Configuring Clay Tablet Languages"](#) on page 16
 - ["Configuring Global Translation Settings"](#) on page 18
 - ["Configuring Lionbridge Freeway Authentication"](#) on page 20
 - ["Configuring SDL TMS Entries"](#) on page 22
 - ["Viewing and Testing Eloqua Authentication Settings"](#) on page 24
 - ["Configuring Translation Settings"](#) on page 26
 - ["Configuring Translation Settings for Eloqua Dynamic Content"](#) on page 30
 - ["Configuring Translation Providers"](#) on page 36
3. Configure users, teams, and access, as described in ["Configuring User Access"](#) on page 40.

5.1 Configuring Clay Tablet Languages

You configure the Clay Tablet languages so that:

- The Lionbridge App correctly identifies the source and target languages of your content.
- The Lionbridge App displays languages in the optimal order for your end users.


To configure Clay Tablet languages:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see ["Viewing Lionbridge App Information and Usage Data"](#) on page 57.

2. Click **Map Languages**.

The **Language Mapping** dialog box opens.

- The top-left corner of the dialog box displays the number of mappings between Eloqua languages and Clay Tablet languages.
- The top-right corner of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.






By default, the Lionbridge App includes predefined mappings between Microsoft locales used by Eloqua, ISO codes, and Clay Tablet language codes.

In CloudBroker, you can modify or delete the current mappings and add new mappings. The following information is displayed about each language mapping:

Column	Description
Language name	The name of the language in Eloqua. For a list of Eloqua language names and codes, see "Appendix: Eloqua Language Codes" .
Code	The Eloqua language's ISO code. For a list of Eloqua names and codes, see "Appendix: Eloqua Language Codes" .
CT language	The Clay Tablet language code for the language. For a list and description of Clay Tablet language codes, see "Appendix: Clay Tablet Language Codes" on page 61.

3. You can modify the following aspects of a language mapping:

- ▶ To map a language to a different Clay Tablet language code, select a language from the dropdown list in the **CT language** column.

- ▶ To change the order in which a language is displayed to your users when they send out content for translation, use the **Move Up**  and **Move Down**  buttons.
- ▶ To remove a language mapping, click the corresponding **Delete** button .

Note: Remove a language mapping does not affect any translation jobs in progress that use that mapping.

4. Optional. To add a new language mapping, click **Add**. The Lionbridge App adds a blank line at the bottom of the list. Enter the language name and ISO code, and select the corresponding Clay Tablet language code from the list.
5. When you are done, click **Save** to save your changes.

5.2 Configuring Global Translation Settings


The Lionbridge App's global translation settings determine how it sends out all translation jobs. These settings include:

- the license for the Lionbridge App and its entry point from within Eloqua
- the source and target languages available for translation
- email notification settings
- whether to use a local translation memory

To set the global translation settings:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.
2. Click **Configure Site**.

The **Site Configuration** dialog box opens, and the **Site Settings** tab is displayed by default. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.



3. Specify the following settings:

Setting	Description
CT License ID	Your company's license for all supported Clay Tablet services. Either Clay Tablet personnel enters this value or you enter this value for your company after you receive it from Clay Tablet.
Entry Point URL	Read only. The URL of the default entry point for the Lionbridge App for Oracle Eloqua in CloudBroker.
Available Source Languages	Select the check boxes for the languages that users can select as the source language when sending out content for translation. The list displays all mapped languages. <ul style="list-style-type: none"> ■ The list displays the Microsoft locale and ISO code for each mapped language. ■ Total indicates the number of languages that are currently selected.

Setting	Description
Available Target Languages	Select the check boxes for the languages that users can select as a target language when sending out content for translation. The list displays all mapped languages. <ul style="list-style-type: none"> ■ The list displays the Microsoft locale and ISO code for each mapped language. ■ Total indicates the number of languages that are currently selected.
Email Notification – Translation Job Sent	Select this check box to send out an email notification when a user sends out a job for translation. The Lionbridge App sends the notification to the user who sent out the job.
Email Notification – Translation Job Completed	Select this check box to send out an email notification when a translation job is completed. The Lionbridge App sends the notification to the user who sent out the job.
Email Notification – Send to Team Members as Well	Select this check box to send out an email notification to all users in the team when: <ul style="list-style-type: none"> ■ A user in the team sends out a job for translation. ■ A translation job that was sent out by a user in the team is completed.
From Email Address	The email address from which the Lionbridge App notification emails will be sent. The default email address is <code>notifications@clay-tablet.com</code> .
Translation – Use Local TM	Translated content is stored in a local translation memory (TM). This setting determines whether to check previously translated content in the local TM for any content changes, and send only changed content out for translation. If content was previously translated and it has not changed, then the Lionbridge App does not send it for translation again: Instead, it uses the stored translation. This feature reduces the quantity of content that the Lionbridge App sends to translation providers, which reduces your cost. However, it increases the processing time before sending out the items for translation.

4. Click **Save**.

5.3 Configuring Lionbridge Freeway Authentication

Note: This section is relevant only if Lionbridge Freeway is your translation provider.

If Lionbridge Freeway is your translation provider, you can configure authentication to Lionbridge Freeway from the Lionbridge App. This facilitates delivering your content from the Lionbridge App, via the Clay Tablet Platform, to Lionbridge Freeway.

To configure Lionbridge Freeway authentication:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.

2. Click **Configure Site**.

The **Site Configuration** dialog box opens. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.

3. Click the **Options for LSP: Freeway** tab.

The screenshot shows a 'Site Configuration' dialog box with the following details:

- Site Name:** My test
- Tabs:** Site Settings, Options for LSP: Freeway (selected), Options for LSP: SDL TMS, Eloqua
- Translation Provider:** Support Freeway (checked)
- Freeway Auth URL:** https://fwapi.lionbridge.com/obvibundles/freewayauth.asmx
- Freeway Service URL:** https://fwapi.demo.lionbridge.com/obvibundles/service.asmx
- Login Username:** enter freeway login username here
- Login Password:** enter freeway login password here
- Buttons:** Test (next to password field), Save (bottom right)

4. To enable support for the Lionbridge Freeway translation provider, select the **Support Freeway** check box.
5. Specify the following Lionbridge Freeway settings:

Setting	Description
Freeway Auth URL	The URL for Lionbridge Freeway authentication.
Freeway Service URL	The URL for the Lionbridge Freeway server.
Login Username	The login name for the Lionbridge Freeway server.
Login Password	The login password for the Lionbridge Freeway server.

6. Click **Save**.


5.4 Configuring SDL TMS Entries

Note: This section is relevant only if SDL TMS is your translation provider.

If SDL TMS is your translation provider, you can configure SDL TMS configuration entries, which are used for submitting translation jobs, via the Clay Tablet Platform, to SDL TMS.



To configure SDL TMS settings:


1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.
2. Click **Configure Site**.
The **Site Configuration** dialog box opens. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.
3. Click the **Options for LSP: SDL TMS** tab.



4. To enable support for the SDL TMS translation provider, select the **Support SDL TMS** check box.
5. Enter the following information about an SDL TMS configuration entry, which is used for submitting translation jobs to SDL TMS:

Column	Description
Group	The Dropbox selection group.
Name	The name to display in the Dropbox selection box.
Key	The key for submitting a job to SDL TMS.
GUID	The key from the Dropbox selection box links to a GUID in SDL TMS. Each GUID is related to a different TM (translation memory), TermBase, and Workflow.

6. Optional. Modify the order of a configuration entry. To change the order in which an entry is displayed to your users when they send out content for translation, use the **Move Up**  and **Move Down**  buttons.


7. Optional. To remove a configuration entry, click the corresponding **Delete** button  .
8. Click **Save**.

5.5 Viewing and Testing Eloqua Authentication Settings

The Lionbridge App must authenticate with Oracle Eloqua. You can view and test the authentication settings in the **Authentication** section of the Eloqua tab of the Site Configuration dialog box. For a detailed description of the other settings in this tab, see "[Configuring User Access](#)" on page 40.

To view and test these settings:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.
2. Click **Configure Site**.
The **Site Configuration** dialog box opens. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.
3. Click the **Eloqua** tab.



4. You can view the following read-only information in the **Authentication** section:

Field	Description
Type	The type of authentication, which is OAuth2.
CloudApp Client ID	The Client ID (App id) for the Lionbridge App.
CloudApp Client Secret	The secret access token that Eloqua generated for the Lionbridge App.
CloudApp Callback URL	The callback URL registered in Eloqua for the Lionbridge App.

For a detailed description of the other fields in this tab, see "[Configuring User Access](#)" on page 40.

5. Optional. You can test the authentication settings.
 - a. Enter values to test. These values are only for testing. They are not saved.

Field	Description
Eloqua Username	You can enter an Oracle Eloqua username to test the authentication settings you entered above.
Eloqua Password	You can enter a password for the Oracle Eloqua username to test the authentication settings you entered above.

- b. Click the **Test** button.

A message box indicates that the test was successful. Click **OK** to close the message box.

6. Close the dialog box.

5.6 Configuring Translation Settings

You can configure the following types of translation settings in the the **Translation Settings** tab of the **Site Configuration** dialog box.

- Whether the Lionbridge App includes the **From Name** field, email header, and/or email footer in Email assets that it sends for translation (in the **Email Translation** section).
- The filename format of the source assets that the Lionbridge App sends out for translation (in the **Asset Name for Translation** section) . By default this is `[{AssetType} : {AssetId}] {AssetName} ({T:ll-cc})`, for example: `[Email:127]My testmail(fr-CA)`. The Lionbridge App has a default *translation-asset-name* handler that supports some predefined building blocks. You can modify the default filename format either by using either the building blocks or a custom handler.
- The filename format of the target assets that the Lionbridge App receives from translation (in the **Translated Asset Name** section). By default this is `[{T:ll-cc}] {AssetName}`, for example: `[(fr-CA)] My test mail`. The Lionbridge App has a default *translated-asset-name* handler that supports some predefined building blocks. You can modify the default filename format either by using either the building blocks or a custom handler.
- The location of the target assets that the Lionbridge App receives from translation (in the **Translated Asset Location** section). The Lionbridge App has a default *translated-asset-location* handler that uploads translated assets to Eloqua under the `{CT_Translated}` sub-folder of the folder where source assets are located. You can use a custom handler to change this default location.
- The format of email notifications that the Lionbridge App sends when a translation job is completed (in the **Notification Format for Translation Completed** section).

To configure these settings:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed

information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.

2. Click **Configure Site**.

The **Site Configuration** dialog box opens. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.

3. Click the **Translation Settings** tab.

Site Configuration

Site Name: **My test**

Site Settings | Options for LSP: Freeway | Options for LSP: SDL TMS | Eloqua | **Translation Settings**

Email Translation Translate [From Name] field Translate [Email Header] Translate [Email Footer]

Asset Name For Translation

Format:

Supported Tags: {AssetName}, {AssetType}, {AssetId}, {TranslatedAssetId}, {S.II-cc}, {T.II-cc}, {S.II}, {T.II}, {S.cc}, {T.cc}

Custom Handler Class:

Translated Asset Name

Format:

Supported Tags: {AssetName}, {AssetType}, {AssetId}, {TranslatedAssetId}, {S.II-cc}, {T.II-cc}, {S.II}, {T.II}, {S.cc}, {T.cc}

Custom Handler Class:

Translated Asset Location

Default: Translated assets will be created under {CT_Translated} sub-folder
Configure your own handler if translated assets need to be uploaded to other location(s)

Custom Handler Class:

Notification Email Format for Translation Completed

Supported Tags: {JobName}, {UserName}, {CreatedDate}, {SourceEloquaAssetURL}, {TargetEloquaAssetURL}, {ItemName}, {AssetName}, {AssetType}, {AssetId}, {TranslatedAssetId}, {S.II-cc}, {T.II-cc}, {S.II}, {T.II}, {S.cc}, {T.cc}

Email Subject:

Email Body:

```
<table style="font-size: 11px; color: #000000;"><tr><td> Translation job: </td><td>
{JobName}</td></tr><tr><td> Created by: </td><td> {UserName}</td></tr><tr>
<td> Created at: </td><td> {CreatedDate}</td></tr><tr><td> Asset Type: </td><td>
{AssetType}</td></tr><tr><td> Asset Name: </td><td> {AssetName}</td></tr><tr>
<td> Asset Id: </td><td> {AssetId}</td></tr><tr><td> Translated Asset Id: </td><td>
{TranslatedAssetId}</td></tr><tr><td> Eloqua Source Asset: </td><td>
```

Save

4. Optional. Depending on what you want to configure, do one or more of the following:

- In the **Email Translation** section, you can select the following check boxes:

- ☒ Select the **Translate [From Name] Field** check box to configure the Lionbridge App to include the **From Name** field in Email assets that it sends for translation.
- ☒ Select the **Translate [Email Header]** check box to configure the Lionbridge App to include the email header in Email assets that it sends for translation.
- ☒ Select the **Translate [Email Footer]** check box to configure the Lionbridge App to include the email footer in Email assets that it sends for translation.
- ☒ In the **Asset Name for Translation** section, in the **Format** field, you can use the building blocks in the table below to specify the filename format of asset files sent out for translation. The default format is `[{AssetType} : {AssetId}] {AssetName} ({T:ll-cc})`, for example: `[Email:127]My testmail (fr-CA)`.
- ☒ In the **Translated Asset Name** section, in the **Format** field, you can use the building blocks in the table below to specify the filename format of translated asset files. The default format is `[{T:ll-cc}] {AssetName}`, for example: `[(fr-CA)] My test mail`.
- ☒ In the **Notification Format for Translation Completed** section, you can use HTML or use the following building blocks

Building Block	Description	Example
{AssetType}	A type of asset.	Email
{AssetId}	Clay Tablet's internal identifier for the asset.	111
{AssetName}	The name of the asset that is displayed in Eloqua.	My test mail
{JobName}	* The name of the translation job.	My job
{UserName}	* The Oracle Eloqua username.	Jen.Smith

Building Block	Description	Example
{CreatedDate}	* The date that the asset was created in Eloqua, in the following format: MM/DD/YYYY Y hh:mm AM/PM.	07/05/2017 11:03 AM
{SourceEloquaAssetURL}	* The URL of the source asset in Eloqua.	https://secure.mycompany.eloqua.com/Main.aspx#forms&id=123
{TargetEloquaAssetURL}	* The URL of the source asset in Eloqua.	https://secure.mycompany.eloqua.com/Main.aspx#forms&id=456
{ItemName}	* The full path of the asset.	Emails/My email message
{TranslatedAssetId}	* Clay Tablet's internal identifier for the translated asset.	222
{S:ll-cc}	The language code and the country code of the source language, separated by a hyphen.	en-CA

Building Block	Description	Example
{S:ll}	The language code only of the source language.	en
{S:cc}	The country code only of the source language.	CA
{T:ll-cc}	The language code and the country code of the target language, separated by a hyphen.	fr-CA
{T:ll}	The language code only of the target language.	fr
{T:cc}	The country code only of the target language.	CA

Note about * : These building blocks are relevant and supported only for email notification formats.

5. Optional. If you want to configure a custom handler, contact Clay Tablet Support. For details, see "[How to Contact Clay Tablet Support](#)" on page 9.
6. Optional. Enter the full class name of each handler in the **Custom Handler Class** field of the relevant section. If this field is blank, the Connector uses the default handler.
7. Click **Save**.

5.7 Configuring Translation Settings for Eloqua Dynamic Content

In Eloqua, *dynamic content* is customer-specific content that changes depending on who is viewing it. For more information about this feature, refer to the *Oracle Eloqua Marketing Cloud Service User's Guide*, available at https://docs.oracle.com/cloud/latest/marketingcs_gs/docs.htm.

When the Lionbridge App collects emails and landing pages to send out for translation, it automatically collects any referenced dynamic content. You can change this behavior, for example, if you do not want to translate some dynamic content, or if you want to translate some dynamic-content rules into specific languages.

To configure translation settings for Eloqua dynamic content:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see "[Viewing Lionbridge App Information and Usage Data](#)" on page 57.
2. In the **Site Extensions** section, click **Configure**.


The **Site Extension** dialog box opens, displaying the **Dynamic Content Translation** tab.




3. Click **Add**.

The **Translation Setting** tab opens.

Note: The Eloqua sign-in page is displayed in this tab only if you are not currently signed in to Eloqua as an end-user. This sign-in page is not displayed in the following scenarios: if you signed in to Eloqua, clicked the


More Apps button  and opened the Lionbridge App from the **Apps** area; if you logged into CloudBroker from the Lionbridge App with end-user credentials (not with site administrator credentials).




The screenshot shows a dialog box titled "Site Extension" with a close button (X) in the top right corner. Below the title bar, it says "Site Name: QA Demo". There are two tabs: "Dynamic Content Translation" and "Translation Setting", with the latter being the active tab. The main content area contains a message: "Please log in to Eloqua to retrieve dynamic content". Below this message are three input fields: "Company" with the text "TechnologyPartnerClayTabletTechnologies", "Username" (empty), and "Password" (empty). Each of the last two fields has a small icon on the right side. Below the input fields is a "Sign In" button. In the bottom right corner of the dialog box is a "Close" button.

4. If the Eloqua sign-in page is displayed in this tab, then enter your Eloqua credentials, and click **Sign In**. This enables the Lionbridge App to retrieve all dynamic content and its rules from Eloqua. If the sign-in page is not displayed, proceed to the next step.


The **Translation Settings** tab updates.



5. Select the dynamic content from the **Dynamic Content** dropdown list.




The **Translation Settings** tab updates for the selected dynamic content to display a row for each rule in the dynamic content, plus one additional row.




6. For each displayed row, create a translation setting for each rule: (In Eloqua, a *rule* is a content option for the dynamic content.)

- In the **Rule** column, select a rule in the dynamic content.
- In the **Action** column, specify the Lionbridge App's action for this rule, either:
 - Ignore: The Lionbridge App *will not* send out this rule for translation for the specified languages.
 - Allow: The Lionbridge App *will* send out this rule for translation for the specified languages.
- In the **Language** column, select the check boxes for the language codes for this setting.
 - For example, if Ignore is selected, then the Lionbridge App *will not* send out this rule for translation in the selected languages.
 - For example, if Allow is selected, then the Lionbridge App *will* send out this rule for translation in the selected languages.

This column displays all languages that are set up for your team, as well as an [--All--] check box to facilitate selecting all languages.



Tip: To prevent the Lionbridge App from sending out any rules in dynamic content for translation, in the **Rule** column, select [--All--], in the **Action** column, select Ignore, and in the **Language** column, select the [--All--] check box.



Note: If there are multiple and conflicting settings for the same rules, then the Lionbridge App prioritizes the settings with the **Ignore** actions over those with the **Allow** actions. For example, if the CN Rule rule is set to ignore all language but to allow the zh-CN language, then the Lionbridge App ignores all languages and does not send out any dynamic content for translation.

7. Click **Save** to save the translation settings for the specified dynamic content and its rules.
8. Repeat steps 3 and 5-7 to specify translation setting for each dynamic content and its rules.

Note: You are not prompted to re-enter your Eloqua credentials (step 4) each time.

5.8 Configuring Translation Providers

Very important: Do not copy the CMS address keys to multiple Oracle Eloqua instances, because this is a violation of the Clay Tablet License Agreement. Using the same CMS address keys on multiple Oracle Eloqua

instances will cause the Connector to behave unexpectedly, which can result in lost translation content, orphaned projects, and inaccurate translation status reports. Clay Tablet will support technical issues caused by duplicating or incorrectly installing CMS address keys only on a time and materials basis.

- The Lionbridge App uses the CMS address key, which is in `source.xml`, to move your items for translation from the Lionbridge App to the Clay Tablet Platform. The Platform then forwards the items to translate to your translation provider. If you are using multiple translation providers, there must be one key (file) for each provider.

Note: The Lionbridge App always initiates calls to the Clay Tablet Platform. However, the CMS address keys enable establishing a secure, discrete connection between the Lionbridge App instance and the Platform. They also support the return of files from translation.

- Your company's platform key is in `target.xml`. This is your company's license for the Clay Tablet Platform. Before you can send assets for translation, you must set up your Clay Tablet license key and your translation providers.

Important: Before starting, ensure you obtain your license key from Clay Tablet. Verify that Clay Tablet has set up your *account license keys* for each of your translation providers.

To configure translation providers:

1. In the **Site Administration** menu on the left, click **Site Providers**.

The **Site Providers** page opens, displaying the translation providers configured for your Oracle Eloqua site.

Site Providers						New Provider	
	Name	Type	Source Account	Platform Account	Used By Team	Actions	
1	My test eloqua provider	Generic	CloudBroker-QA-Test	ctf-testing-platform	Lionbridge team	Edit	Delete

2. To create a new translation provider, click **New Provider**.

Notes: To update the account license keys for a current translation provider, click **Edit** for that translation provider. To delete a translation provider, click **Delete** for that translation provider. A message box prompt you to confirms that you want to delete this translation provider. Click **OK** to proceed.

The **New provider** dialog box opens.

Note: If you clicked **Edit**, the **Edit Provider** dialog box opens instead. Aside from the title, it is identical to the dialog box described below.

New Provider

Provider Name: Default-Provider

Provider Type: Generic

Licensed Keys: CloudBroker_Eloqua_QA (Server:ip-10-30-20-147 IP:10.30.20.1) Retrieve

Source XML:


```
<com.claytablet.model.event.Account>
<id>CloudBroker_Eloqua_QA</id>
<createDate>2015-07-10 13:21:32.118 UTC</createDate>
<producerId>CloudBroker_Eloqua_QA</producerId>
<active>true</active>
<email>CloudBroker_Eloqua_QA@clay-tablet.net</email>

<publicKey>Ud3X+MyYGFOAtR3JxNfX7YLZnlMgBmD4</publicKey>

<privateKey>pVKGWyXMGj8DyUKoqXwg7ZN888qcSoumbchXU9J
fpj1/J7gYBuyb3WGFyyJ7Flek</privateKey>
<queueType>SQS</queueType>

<queueEndpoint>https://queue.amazonaws.com:443/286893291
437/CloudBroker_Eloqua_QA</queueEndpoint>
```

 Test

Platform XML:


```
<com.claytablet.model.event.Account>
<id>ctt-testing-platform</id>
<createDate>2013-10-29 11:33:02.968 EDT</createDate>
<active>true</active>
<email>ctt-testing-platform@clay-tablet.net</email>
<publicKey>QMYE9vSyK9g66kq4WDszmu60d5p1EJq</publicKey>

<privateKey>b6qQ8PpbmNRwFdUMDrqWkktocDy163/mnY9/fWVQ13
13MTZgve7AGGFyyJ7Flek</privateKey>
<queueType>SQS</queueType>

<queueEndpoint>https://queue.amazonaws.com:443/699879044544
/ctt-testing-platform</queueEndpoint>
<storageType>S3</storageType>
<storageBucket>ctt-testing-platform</storageBucket>
</com.claytablet.model.event.Account>
```

 Test

Save

- In the **Provider Name** field, enter the name of the translation provider.
- In the **Provider Type** dropdown list, select the type of translation provider. This supports sending translation metadata to specific translation providers. If you do not see your translation provider, select **Generic**.
- In the **Licensed Keys** dropdown list, select the license key for the translation provider. This is the license key that Clay Tablet personnel set up for your company for a particular translation provider on the Clay Tablet License Server. Depending on the number of license keys configured for you on the Clay Tablet license server (and specified by your **CT License ID**, in the **Site Settings** tab of the **Site Configuration** dialog box), multiple license keys may be displayed.
- Click **Retrieve**.
This populates the **Source XML** and **Platform XML** boxes.
 - ☛ The **Source XML** box has the CMS address key, which the Lionbridge App uses to move your assets from Oracle Eloqua to the Clay Tablet Platform.
 - ☛ The **Platform XML** box has the platform key, for accessing the Clay Tablet Platform.
- Click **Test** beside the **Source XML** box. A message box indicates whether this key passed the test.

- f. Click **Test** beside the **Platform XML** box. A message box indicates whether this key passed the test.
3. Click **Save**.

6 Configuring User Access

Any Oracle Eloqua user who is added to CloudBroker can access the Lionbridge App. However, to send out content for translation from the Lionbridge App, a user must be part of a team. A user's *team* determines:

- the *source languages* of the assets that a user can send out for translation
- the *target languages* into which a user can request translation of the assets
- the *translation providers* to whom a user can send the assets for translation

An Oracle Eloqua user also requires specific user permissions in Eloqua to send out content for translation from the Lionbridge App. For a list of the minimal recommended permissions, refer to the Eloqua documentation, available at: <https://community.oracle.com/docs/DOC-895414>. Specifically, download the `OoBSecurityGroups_Permissions.xlsx` file on that page, and ensure that the user has the permissions listed in the **Advanced Users - Marketing** column in that file.

Who can access the Lionbridge App

There are multiple ways to add Oracle Eloqua users to CloudBroker so that they can access Lionbridge App:

Method for Adding Eloqua Users	Advantage	Disadvantage	How To...
Automatically allow all Oracle Eloqua users to access the Lionbridge App and add them to the default team.	When an Oracle Eloqua user accesses the Lionbridge App, CloudBroker automatically adds the user to the default team. This is particularly useful if you want all Oracle Eloqua users to have access to the Lionbridge App, and you only want to use one team.	Either: <ul style="list-style-type: none"> ■ All Oracle Eloqua users only use one team, so all users can send to all configured source and target languages and translation providers. ■ You must move users from the default team to appropriate teams configured source and target languages and translation providers. 	In the Eloqua tab of the Site Configuration dialog box, select the Allow All Eloqua Users to Manage Translations check box, and specify a Default Team , as described below.

Method for Adding Eloqua Users	Advantage	Disadvantage	How To...
Import users from Oracle Eloqua into CloudBroker.	You select which Oracle Eloqua users to import into CloudBroker.	You must add imported users to a team, even if you want to use a single team.	In the Site Users page, click Import Users , and select the users to import. For detailed instructions, see "Importing Users" on page 49.
Add individual Oracle Eloqua users to CloudBroker.	This is useful if you want only a few Oracle Eloqua users to access the Lionbridge App.	It is very time consuming to individually add each user to CloudBroker.	In the Site Users page, click New User . For detailed instructions, see "Adding a User" on page 52.

Note: When Oracle Eloqua users access the Lionbridge App, it must authenticate with the Oracle Eloqua server.

To configure user access:

1. In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator. For detailed information about this page, see ["Viewing Lionbridge App Information and Usage Data"](#) on page 57.
2. Click **Configure Site**.
The **Site Configuration** dialog box opens. The **Site Name** field at the top of the dialog box displays the name that Clay Tablet personnel assigned to your company's site.
3. Click the **Eloqua** tab.

The screenshot shows the 'Site Configuration' window for a site named 'My test'. It has four tabs: 'Site Settings', 'Options for LSP: Freeway', 'Options for LSP: SDL TMS', and 'Eloqua'. The 'Access' section is highlighted with a red rounded rectangle and contains the following elements:

- Eloqua Users**: A checked checkbox labeled 'Allow All Eloqua Users to Manage Translations'.
- Default Team**: A dropdown menu currently showing 'Lionbridge team'.

The 'Authentication' section below it includes:

- Type**: A dropdown menu set to 'OAuth2'.
- CloudApp Client ID**: A text field containing '6dc96a95-89e-4078-8a01-e7a8574d0fc2'.
- CloudApp Client Secret**: A text field containing '1-Wv-vuuFHkSgR-rTFpNqODUJYKW590EV-napVHDlnINTqBP-8TMxX2Eg67x8HISPvYsnGOKPtn5E-B07-3mRe29ddRz5pn1FG'.
- CloudApp Callback URL**: A text field containing 'https://cb1.ops.na.clay-tablet.net/CloudBroker/plugins/eloqua/callback'.
- A **Test** button.
- A note: 'These inputs are only required if you need to test Eloqua OAuth2 connection, and will not be saved.'
- Eloqua Username**: A text input field with the placeholder 'enter Eloqua username here'.
- Eloqua Password**: A text input field with the placeholder 'enter Eloqua password here'.

A **Save** button is located at the bottom right of the window.

4. Enter the following information in the **Access** section:

Field	Description
Eloqua Users – Allow All Eloqua Users to Manage Translations	Select this check box to enable all Oracle Eloqua users to access the Lionbridge App. CloudBroker then automatically adds each user to the team configured as the default team, which means it is selected in the Default Team dropdown list, described below. Note: If you do not select this check box, you must add each Oracle Eloqua user who is allowed to access the Lionbridge App, either individually or by importing from Oracle Eloqua. You must also add each user who can send out content for translation to a team. For detailed instructions, see "Adding a User" on page 52 and "Importing Users" on page 49.

Field	Description
Default team	<p>If you select the Allow All Eloqua Users to Manage Translations check box, described above, CloudBroker automatically adds all Oracle Eloqua users to the team specified here. You can create teams, so that they will be available for selection here. For details, see "Adding or Editing a Team" on page 44.</p> <p>Note: This dropdown list is available for selection only if the Allow All Eloqua Users to Manage Translations check box, described above, is selected.</p>

For a detailed description of the other fields in this tab, see ["Viewing and Testing Eloqua Authentication Settings"](#) on page 24.

- Click **Save**.

6.1 Managing Teams

A *team* is a collection of users for a specific site. All users on a team can send out content for translation from the source languages to the translation providers into the target languages configured for the team.

Important: Before setting up users and teams, read ["Configuring User Access"](#) on page 40.

This section describes how to view information about existing teams, add a new team, and edit an existing team.

To manage teams:


- In the **Site Administration** menu on the left, click **Site Teams**.

The **Site Teams** page opens, displaying the teams of users set up for your Eloqua site.

Site Teams						New Team
	Name	Source Languages	Target Languages	Providers	Total Users	Actions
1	abcd	en-US	af-ZA, de-DE, hi-IN		1	Edit Delete
2	Lionbridge team	en-US	af-ZA, de-DE, es-ES, fr-FR, hi-IN, ja-JP, zh-CN	My test eloqua provider	13	Edit Delete

This page displays the following information about each team:

Column	Description
Name	The name of a team.
Source Languages	The source languages of the content that users in this team can send out for translation.

Column	Description
Target Languages	The target languages of the content to which users in this team can send out content for translation.
Providers	The translation providers to which users in this team can send out content for translation.
Total Users	The total number of users in this team. Tip: To view the users in this team, click the  icon. The Team users box displays all the users on the team and their email addresses.

2. Do one of the following:

- ▶ To create a new team, click **New Team**. For detailed instructions, see ["Adding or Editing a Team"](#) on page 44.
- ▶ To edit a team, in the **Actions** column, click **Edit** in the corresponding row. For detailed instructions, see ["Adding or Editing a Team"](#) on page 44.
- ▶ To delete a team, in the **Actions** column, click **Delete** in the corresponding row. For detailed instructions, see ["Deleting a Team"](#) on page 47.

6.1.1 Adding or Editing a Team

You can create a new team or edit a team that was created previously.

To add or edit a team:

1. In the **Site Administration** menu on the left, click **Site Teams**.

The **Site Teams** page opens, displaying the teams set up for your Eloqua site. For detailed information about this page, see ["Managing Teams"](#) on page 43.

2. Do one of the following:

- ▶ To create a new team, click **New Team**.
- ▶ To edit an existing team, click **Edit** for that team.


Either the **New Site Team** or the **Edit Site Team** dialog box opens, displaying the **Source Languages** tab. Other than the title, these dialog boxes are nearly identical.

The screenshot shows the 'New Site Team' dialog box with the 'Source Languages' tab selected. At the top, there is a 'Team Name' field with the placeholder text 'enter team name here'. Below this are four tabs: 'Source Languages', 'Target Languages', 'Providers', and 'Users'. The 'Source Languages' tab is active, showing a list of source languages. The list is currently empty, with 'Total: 0' displayed above it. A single entry, 'en-US (English_United States)', is visible in the list, with a checkbox to its left. An 'Add' button is located at the bottom right of the dialog box.


3. In the **Team Name** field, enter the name for your team.
4. Select the check boxes for the source languages that users on this team can send out for translation.
5. Click the **Target Languages** tab.

The screenshot shows the 'New Site Team' dialog box with the 'Target Languages' tab selected. The 'Team Name' field and the other tabs are the same as in the previous screenshot. The 'Target Languages' tab is active, showing a list of target languages. The list is currently empty, with 'Total: 0' displayed above it. A list of target languages is visible, each with a checkbox to its left: 'af-ZA (Afrikaans_South Africa)', 'de-DE (German_Germany)', 'es-ES (Spanish_Spain)', 'fr-FR (French_France)', 'hi-IN (Hindi_India)', 'ja-JP (Japanese_Japan)', and 'zh-CN (Chinese_Simplified,P.R.China)'. An 'Add' button is located at the bottom right of the dialog box.

6. Select the check boxes for the target languages to which users on this team can send out content for translation. Users on the team are allow to send content for translation *into* these target languages.
7. Click the **Providers** tab.



8. Select the check boxes for the translation providers to which the users on this team can send out content for translation.
9. Click the **Users** tab.



10. Select the check boxes for the users who are on this team.
11. Do one of the following to save your changes:
 - ▶ In the **New Site Team** dialog box, click **Add**.
 - ▶ In the **Edit Site Team** dialog box, click **Save**.

Important: You can set this team to the default team. A default team is required if you select the **Allow All Eloqua Users to Manage Translations** check box in the **Eloqua** tab of the **Site Configuration** dialog box. For details, see "[Configuring User Access](#)" on page 40.

6.1.2 Deleting a Team

You can delete a team from the Lionbridge App so that it will no longer be a collection of users with the same permissions for sending out assets for translation from specified source languages, to specified target languages, to specified translation providers.

Important: Deleting a team from the Lionbridge App also deletes all the jobs and items sent by users from the Lionbridge App *as part of this team*. Deleting a team from the Lionbridge App does not delete the users in the team from either CloudBroker or Oracle Eloqua.

Notes about users that are in multiple teams: Deleting a team does not delete jobs or items that users sent as part of a different team. If users are in multiple teams, deleting a team from the Lionbridge App does not change user permissions from the non-deleted team.


To delete a team from the Lionbridge App:

1. In the **Site Administration** menu on the left, click **Site Teams**.

The **Site Teams** page opens, displaying the teams set up for your Oracle Eloqua site. For detailed information about this page, see "[Managing Teams](#)" on page 43.

2. In the **Actions** column, click **Delete** for the team to delete.

The **Delete Team** dialog box opens.



The dialog box displays the name of the team to delete. It also displays the following information about the jobs and items that users on this team sent for translation, as part of this team:

Field	Description
Total Jobs	The total number of jobs users on this team sent out for translation.
Total Translation Items	The total number of items users on this team sent out for translation.

Field	Description
Total Completed	The total number of translated items that the Lionbridge App has re-imported into Oracle Eloqua.
Total Incomplete	The total number of assets that the Lionbridge App has not yet re-imported into Oracle Eloqua. Usually these are assets that are currently in translation, or were just recently received back from translation and that the Lionbridge App is trying to re-import into Oracle Eloqua. Warning: If you delete this team, these items will be deleted. They will not be re-imported into Oracle Eloqua.

- Click **Delete** to remove the team and all the jobs and items sent out for translation by users as part of this team from the Lionbridge App.

6.2 Managing Users

Eloqua users can access Lionbridge App to send, monitor, and review translation jobs.

Important: Before setting up users and teams, read "[Configuring User Access](#)" on page 40.

To manage users:

- In the **Site Administration** menu on the left, click **Site Users**.

The **Site Users** page opens, displaying the users set up for your Oracle Eloqua site.

	Name	Email Address	Default Language	Teams	Site Admin	Actions
1	[Redacted]	[Redacted]@lionbridge.com	en	Lionbridge team		Edit Delete
2	[Redacted]	[Redacted]@lionbridge.com	en	Lionbridge team		Edit Delete
3	[Redacted]	[Redacted]	[Redacted]	[Redacted]		[Redacted]
10	QA.Test	qa.test@clat-tablet.com	en	Lionbridge team		Edit Delete
11	QA.Test2	QA.Test2@clat-Tablet.com	en	Lionbridge team	✓	Edit Delete

This page displays the following information about each user:

Column	Description
Name	The name of the user.

Column	Description
Email Address	The email address of the user.
Default Language	The default language in which the Lionbridge App interface is displayed for the user. If the user is a site administrator, who can access the functionality described in this guide, then this is the language in which the CloudBroker interface is displayed for this user.
Teams	The teams to which this user belongs. The team determines which source and target languages the user can send out for translation and the translation providers to which the user can send the content.
Site Admin	A check mark indicates whether this user is a site administrator. Site administrators can access CloudBroker to set up the Lionbridge App, as described in this guide.

2. Do one of the following:

- ▶ To create a new user, click **New User**. For detailed instructions, see ["Adding a User"](#) on page 52.
- ▶ To import users, click **Import Users**. For detailed instructions, see ["Importing Users"](#) on page 49.
- ▶ To edit a user, in the **Actions** column, click **Edit** in the corresponding row. For detailed instructions, see ["Editing a User"](#) on page 50.
- ▶ To delete a user, in the **Actions** column, click **Delete** in the corresponding row. For detailed instructions, see ["Deleting a User"](#) on page 55.

6.2.1 Importing Users

You import users from Oracle Eloqua to the Lionbridge App so that you can add them to teams, which enables them to send assets for translation from and to specified languages and to specified translation providers. This is the best way to add *many* Oracle Eloqua users to the Lionbridge App without adding *all* the users to the App.

Important: Before setting up users and teams, read ["Configuring User Access"](#) on page 40.


To import users:

1. In the **Site Administration** menu on the left, click **Site Users**.

The **Site Users** page opens, displaying the users set up for your Oracle Eloqua site. For detailed information about this page, see ["Managing Users"](#) on page 48.

2. Click **Import Users**.

A dialog box may open, prompting you to log in to Oracle Eloqua.



3. If the dialog box opens, enter your Oracle Eloqua credentials, and click **Login**.

The **Import Users** dialog box opens, displaying all your Oracle Eloqua users that are not already in CloudBroker.



4. Select the check boxes for the users to import into the Lionbridge App, and then click **Import**.

The Lionbridge App imports each selected user's username and email address.

Note: After users are imported, you still need to add them to a team, so that they can send out assets for translation. You can also specify which users are site administrators, who can access configuration and administration features in the Lionbridge App, and you can specify the default language for displaying the Lionbridge App to each user. For details, see the following section, "[Editing a User](#)".

6.2.2 Editing a User

In general you edit a user that you previously added, either by importing or automatically, to specify the following information:

- the default language for displaying the Lionbridge App for the user
- whether the user is a site administrator, who can access CloudBroker to set up the Lionbridge App, as described in this guide
- the teams that the user joins

You can also change a user's username or email address.

To edit a user:

1. In the **Site Administration** menu on the left, click **Site Users**.

The **Site Users** page opens, displaying the users set up for your Oracle Eloqua site. For detailed information about this page, see "[Managing Users](#)" on page 48.

2. Click **Edit** for the user to edit.

The **Edit User** dialog box opens.

3. You can modify the following information:

Field	Description
User Name	The user's username. This must be the same as the user's username for accessing Oracle Eloqua.
User Email	The user's email address.

Field	Description
Default Language	In the dropdown list, select the default language in which the Lionbridge App interface is displayed for the user. If the user is a site administrator, who can access the functionality described in this guide, then this is the language in which the CloudBroker interface is displayed for this user. Languages are configured in CloudBroker by Clay Tablet. For more information, please contact Clay Tablet Support, as described in " How to Contact Clay Tablet Support " on page 9.
User Role	<p>Indicates whether this user is a site administrator, who can access CloudBroker to set up the Lionbridge App, as described in this guide.</p> <ul style="list-style-type: none"> ■ If the user is a site administrator, select the Is Site Admin check box. ■ If the user is not a site administrator, clear the Is Site Admin check box. <p>If the user is not a site administrator, you can grant the following administrative permissions to the user by selecting the corresponding check boxes:</p> <ul style="list-style-type: none"> ■ Configure Site: configure your site, in the Site Configuration dialog box. ■ Map Languages: configure language mappings, in the Language Mapping dialog box. ■ Manage Dynamic Content Translation settings: configure translation settings for dynamic content, in the Site Extension dialog box. ■ Manage Providers: configure translation providers, in the Site Providers page. ■ Manage Teams: manage teams, in the Site Teams page. ■ Manage Users: manage users, in the Site Users page. ■ View All Teams' Jobs: view the translation jobs for all teams, in the Site Jobs page. Otherwise, the user can view jobs only for the teams to which the user is assigned. ■ Download Translation Files: download source and target XML translation files, in the Job Details tab of the Translation Jobs page.
Join Teams	<p>The teams to which this user belongs. A user must belong to at least one team to be able to send out content for translation. The team determines which source and target languages the user can send out for translation and the translation providers to which the user can send the content.</p> <p>You can view the settings for all teams on the Site Teams page. For details, see "Managing Teams" on page 43.</p> <ul style="list-style-type: none"> ■ To join a team, select the corresponding check box. ■ To leave a team, clear the corresponding check box.

4. Click **Save** to save your changes.

6.2.3 Adding a User

You can individually add an Oracle Eloqua user to the Lionbridge App so that you can add the user to one or more teams. This enables the user to send assets for translation from and to specified languages and to

specified translation providers.

Individually adding an Oracle Eloqua user to the Lionbridge App is useful if you want only a few Oracle Eloqua users to access it.

Important: Before setting up users and teams, read "[Configuring User Access](#)" on page 40.

To add a user:

1. In the **Site Administration** menu on the left, click **Site Users**.

The **Site Users** page opens, displaying the users set up for your Oracle Eloqua site. For detailed information about this page, see "[Managing Users](#)" on page 48.

2. Click **New User**.

The **New User** dialog box opens.

3. Enter the following information about the new user:

Field	Description
User Name	Enter the user's username for accessing the Lionbridge App. This must be the same as the user's username for accessing Oracle Eloqua.

Field	Description
User Email	Enter the user's email address.
Default Language	In the dropdown list, select the default language in which the Lionbridge App interface is displayed for the user. If the user is a site administrator, who can access the functionality described in this guide, then this is the language in which the CloudBroker interface is displayed for this user. Languages are configured in CloudBroker by Clay Tablet. For more information, please contact Clay Tablet Support, as described in "How to Contact Clay Tablet Support" on page 9.
User Role	<p>Indicates whether this user is a site administrator, who can access CloudBroker to set up the Lionbridge App, as described in this guide.</p> <ul style="list-style-type: none"> ■ If the user is a site administrator, select the Is Site Admin check box. ■ If the user is not a site administrator, clear the Is Site Admin check box. <p>If the user is not a site administrator, you can grant the following administrative permissions to the user by selecting the corresponding check boxes:</p> <ul style="list-style-type: none"> ■ Configure Site: configure your site, in the Site Configuration dialog box. ■ Map Languages: configure language mappings, in the Language Mapping dialog box. ■ Manage Dynamic Content Translation settings: configure translation settings for dynamic content, in the Site Extension dialog box. ■ Manage Providers: configure translation providers, in the Site Providers page. ■ Manage Teams: manage teams, in the Site Teams page. ■ Manage Users: manage users, in the Site Users page. ■ View All Teams' Jobs: view the translation jobs for all teams, in the Site Jobs page. Otherwise, the user can view jobs only for the teams to which the user is assigned. ■ Download Translation Files: download source and target XML translation files, in the Job Details tab of the Translation Jobs page.
Join Teams	<p>Select the check boxes of the teams the user is joining. A user must belong to at least one team to be able to send out content for translation. The team determines which source and target languages the user can send out for translation and the translation providers to which the user can send the content.</p> <p>You can view the settings for all teams on the Site Teams page. For details, see "Managing Teams" on page 43.</p>

4. Click **Add**.

6.2.4 Deleting a User

You can delete a user from the Lionbridge App so that the user will no longer have access. Deleting a user from the Lionbridge App also deletes all the jobs and items sent by this user from the Lionbridge App .

Important: Deleting a user from the Lionbridge App does not delete the user in Oracle Eloqua.

To delete a user from the Lionbridge App:

1. In the **Site Administration** menu on the left, click **Site Users**.

The **Site Users** page opens, displaying the users set up for your Oracle Eloqua site. For detailed information about this page, see "[Managing Users](#)" on page 48.

2. In the **Actions** column, click **Delete** for the user to delete.

The **Delete User** dialog box opens.

The page displays the username and email address of the user to delete. It also displays the following information about the jobs and items this user sent for translation:

Field	Description
Total Jobs	The total number of jobs this user sent out for translation.
Total Translation Items	The total number of items this user sent out for translation.
Total Completed	The total number of translated items that the Lionbridge App has re-imported into Eloqua.

Field	Description
Total Incomplete	The total number of assets that the Lionbridge App has not yet re-imported into Oracle Eloqua. Usually these are assets that are currently in translation, or were just recently received back from translation and that the Lionbridge App is trying to re-import into Oracle Eloqua. Warning: If you delete this user, these items will be deleted. They will not be re-imported into Oracle Eloqua.

3. Click **Delete** to remove the user and all the jobs and items sent out for translation by this user from the Lionbridge App.

7 Administrative Tasks

As a site administrator, you can perform the following administrative tasks:


- ["Viewing Lionbridge App Information and Usage Data"](#) on page 57
- ["Viewing Job Data"](#) on page 59

7.1 Viewing Lionbridge App Information and Usage Data

You can view information about your Lionbridge App site and usage on the **My Site** page in CloudBroker.



To view data about your company's Lionbridge App usage:

- ▶ In the **Site Administration** menu on the left, ensure that **My Site** is selected, so that the **My Site** page is open. This is the default selection when you log into CloudBroker as a site administrator.

My Site							Actions			
Active	Name	Platform	Lionbridge App	Content site name						
1		My test	Public	Lionbridge App for Eloqua	TechnologyPartnerClayTabletTechnologies		Map Languages Configure Site			

Statistics									
Total Jobs	Total Items	Total Items to LSP	Total Sent Out	Total Received	Total Completed	Total LocalTM	Total Providers	Total Site Teams	Total Site Users
31	494	488	488	488	494	724	1	2	13

The top section of the page displays the following information about the Lionbridge App:

Column	Description
Active	<p>The Lionbridge App's current status. This is one of the following:</p> <ul style="list-style-type: none"> ■  Active: The Lionbridge App is currently running. ■  Inactive: The Lionbridge App is not currently running.
Name	The name that Clay Tablet personnel assigned to your company's site.
Platform	<p>The type of Clay Tablet Platform (Platform) that your company site uses. The Platform is the connectivity platform that receives and routes content from content systems to translation providers and back during implementation. There are two types:</p> <ul style="list-style-type: none"> ■ Public: This IaaS (Infrastructure as a Service) solution is hosted on AWS. Clay Tablet configures the Platform based on the number and nature of systems involved in your system architecture. ■ On-Premise: Your company either hosts the Platform or it determines the cloud location that hosts it.

Column	Description
Lionbridge App	The Lionbridge plug-in that connects the Eloqua content system to the Clay Tablet Platform. This is the <code>Lionbridge App</code> for Oracle Eloqua.
Name in Content System Site	This is the company name in Oracle Eloqua.

For information about the **Map Languages** and **Configure Site** buttons, see "[Configuring the Lionbridge App in CloudBroker](#)" on page 16.

The **Statistics** section of the page displays the following information about items processed by the Lionbridge App:

Column	Description
Total Jobs	The total number of translation jobs that the Lionbridge App sent out for translation.
Total Items	The total number of translation requests (each source and target language pair is a separate item) from Lionbridge App users. This includes items the Lionbridge App sent out to a translation provider, items translated by localTM (translation memory) , and items that did not require translation.
Total Items to LSP	The total number of items (each source and target language pair is a separate item) that the Lionbridge App sent out for translation to a translation provider.
Total Sent Out	The total number of files that the Lionbridge App sent out for translation.
Total Received	The total number of files that the Lionbridge App received back from translation.
Total Completed	The total number of items (each source and target language pair is a separate item) for which the translation is complete.
Total LocalTM	The total number of items in the local translation memory's database.
Total Providers	The total number of translation providers configured in the Lionbridge App.
Total Site Teams	The total number of teams set up in the Lionbridge App.

Column	Description
Total Site Users	The total number of users set up in the Lionbridge App.

7.2 Viewing Job Data

You can view data about jobs that the Lionbridge App sends out for translation.

To view job data:

1. In the **Site Administration** menu on the left, click **Site Jobs**.


The **Site Jobs** page opens, displaying all the jobs that the Lionbridge App sent out for translation.

The screenshot shows the 'Site Jobs' page with a search bar and a table of 11 entries. The table columns are Job Name, Creation Date, Created By, Team, Provider, Total, Sent Out, Received, and Completed. The entries are listed in reverse chronological order by creation date.

Job Name	Creation Date	Created By	Team	Provider	Total	Sent Out	Received	Completed
Pat Test 2	2016-06-15 02:19:34 PM	QA.Test	Lionbridge team	My test eloqua provider	7	7	7	7
sample job-test1	2016-05-11 06:39:41 AM	QA.Test2	Lionbridge team	My test eloqua provider	1	1	1	1
MT Sample test 2	2016-05-05 08:04:20 AM	QA.Test2	Lionbridge team	My test eloqua provider	7	7	7	7
MT Sample test 1	2016-05-05 03:15:34 AM	QA.Test2	Lionbridge team	My test eloqua provider	20	20	20	20
sample job for translation	2016-05-04 05:16:34 AM	QA.Test2	Lionbridge team	My test eloqua provider	12	12	12	12
Test panel job	2016-05-02 12:33:35 PM	Lemin.Chen	Lionbridge team	My test eloqua provider	36	36	36	36
Test Bing MT - 5	2016-04-25 01:42:11 PM	Lemin.Chen	Lionbridge team	My test eloqua provider	48	48	48	48
Test BING MT -4	2016-04-25 12:50:23 PM	Lemin.Chen	Lionbridge team	My test eloqua provider	92	92	92	92
Test BING MT - 3	2016-04-25 11:58:35 AM	Lemin.Chen	Lionbridge team	My test eloqua provider	28	28	28	28
Test Bing MT-2	2016-04-25 11:22:36 AM	Lemin.Chen	Lionbridge team	My test eloqua provider	8	8	8	8
test Bing MT	2016-04-25 11:14:44 AM	Lemin.Chen	Lionbridge team	My test eloqua provider	14	14	14	14

This page displays the following information about each job, in reverse chronological order by creation date:

Column	Description
Job Name	The name assigned to the translation job by the user who sent it out for translation.
Creation Date	The date and time when the user sent out this job for translation, in the following format: YYYY-MM-DD hh:mm:ss AM/PM.
Created By	The username of the user who sent out this job for translation.
Team	The team for this translation job, which was specified when the user sent out the job for translation.

Column	Description
Provider	The translation provider for this translation job.
Total	The total number of assets in this translation job.
Sent Out	The number of items in this translation job that the Lionbridge App sent out for translation. Note: There is a separate item for each source and target language pair. For example, if you created a job that sends out a single asset for translation from English to both French and German, then these are two separate items in this tab: English to French, and English to German.
Received	The number of items in this translation job that the Lionbridge App received back from translation.
Completed	The number of items in this translation job for which the translation is complete. If the items have an error, including <code>Failed</code> status, you can hover over the Error icon  to view information about the type of error. If the error is resolved and the items are processed normally, the error icon is no longer displayed.

2. Optional. You can do one or more of the following on this page:

- ▶ You can specify how many items to display in a page. Above the top-left corner of the list, select the number to display from the **Show X Entries** list.
- ▶ You can use the **Search** box above the top-right corner of the list to search for a specific asset in the list or to filter the list. As you type into the **Search** box, the Lionbridge App automatically searches for matches across all columns and displays only the matching assets.

Note: The search feature filters all items in the page, not only those displayed on the current sub-page.

- ▶ If there are many items in this page, it may have multiple sub-pages. The navigation bar below the list helps you navigate through the sub-pages and displays your position in the tab. Click **Previous Page**, **Next Page**, or a page number to navigate to the corresponding sub-page.
- ▶ To sort the items in the tab by a different column, click the corresponding column header.
- ▶ To reverse the sort order of a column, click the column header.

8 Appendix: Clay Tablet Language Codes

For detailed instructions on configuring languages for the Lionbridge App, see ["Configuring Clay Tablet Languages"](#) on page 16.

The Lionbridge App has the following language codes:

Type	Language Identifier	Language Code
String	Afrikaans	"af-ZA"
String	Albanian	"sq-AL"
String	Amharic	"am-ET"
String	Arabic_Algeria	"ar-DZ"
String	Arabic_Bahrain	"ar-BH"
String	Arabic_Egypt	"ar-EG"
String	Arabic_Iraq	"ar-IQ"
String	Arabic_Jordan	"ar-JO"
String	Arabic_Kuwait	"ar-KW"
String	Arabic_Lebanon	"ar-LB"
String	Arabic_Libya	"ar-LY"
String	Arabic_MiddleEast	"ar-XR"
String	Arabic_Morocco	"ar-MA"
String	Arabic_Oman	"ar-OM"
String	Arabic_Qatar	"ar-QA"
String	Arabic_Saudi_Arabia	"ar-SA"
String	Arabic_Syria	"ar-SY"
String	Arabic_Tunisia	"ar-TM"
String	Arabic_UAE	"ar-AE"
String	Arabic_Yemen	"ar-YE"

Type	Language Identifier	Language Code
String	Armenian	"hy-AM"
String	Assamese	"as-IN"
String	Basque	"eu-ES"
String	Belarusian	"be-BY"
String	Bengali_Bangladesh	"bn-BD"
String	Bengali_India	"bn-IN"
String	Bosnian_Bosnia_Herzegovina	"bs-BA"
String	Bulgarian	"bg-BG"
String	Burmese	"my-MM"
String	Catalan	"ca-ES"
String	Chinese_Hong_Kong	"zh-HK"
String	Chinese_Macao	"zh-MO"
String	Chinese_PRC	"zh-CN"
String	Chinese_Singapore	"zh-SG"
String	Chinese_Taiwan	"zh-TW"
String	Croatian	"hr-HR"
String	Croatian_Bosnia_Herzegovina	"hr-BA"
String	Czech	"cs-CZ"
String	Danish	"da-DK"
String	Divehi	"dv-MV"
String	Dutch	"nl-NL"
String	Dutch_Belgium	"nl-BE"
String	English_Australia	"en-AU"

Type	Language Identifier	Language Code
String	English_Belize	"en-BZ"
String	English_Canada	"en-CA"
String	English_HongKong	"en-HK"
String	English_India	"en-IN"
String	English_Indonesia	"en-ID"
String	English_Ireland	"en-IE"
String	English_Jamaica	"en-JM"
String	English_Malaysia	"en-MY"
String	English_New_Zealand	"en-NZ"
String	English_Philippines	"en-PH"
String	English_Singapore	"en-SG"
String	English_South_Africa	"en-ZA"
String	English_Trinidad	"en-TT"
String	English_UK	"en-GB"
String	English_US	"en-US"
String	English_Zimbabwe	"en-ZW"
String	Estonian	"et-EE"
String	Faroese	"fo-FO"
String	Farsi	"fa-IR"
String	Filipino	"fil-PH"
String	Finnish	"fi-FI"
String	French	"fr-FR"
String	French_Belgium	"fr-BE"

Type	Language Identifier	Language Code
String	French_Cameroon	"fr-CM"
String	French_Canada	"fr-CA"
String	French_Cote_d_Ivoire	"fr-CI"
String	French_Democratic_Rep_Congo	"fr-CD"
String	French_Haiti	"fr-HT"
String	French_Luxembourg	"fr-LU"
String	French_Mali	"fr-ML"
String	French_Monaco	"fr-MC"
String	French_Morocco	"fr-MA"
String	French_Reunion	"fr-RE"
String	French_Senegal	"fr-SN"
String	French_Switzerland	"fr-CH"
String	Frisian_Netherlands	"fy-NK"
String	Fulfulde_Nigeria	"ff-NG"
String	FYRO_Macedonian	"mk-MK"
String	Gaelic_Ireland	"gd-IE"
String	Gaelic_Scotland	"gd-GB"
String	Gallegan	"gl-ES"
String	Georgian	"ka-GE"
String	German	"de-DE"
String	German_Austria	"de-AT"
String	German_Liechtenstein	"de-LI"
String	German_Luxembourg	"de-LU"

Type	Language Identifier	Language Code
String	German_Switzerland	"de-CH"
String	Greek	"el-GR"
String	Guarani	"gn-PY"
String	Gujarati	"gu-IN"
String	Hausa	"ha-NE"
String	Hawaiian	"haw-US"
String	Hebrew	"he-IL"
String	Hindi	"hi-IN"
String	Hungarian	"hu-HU"
String	Icelandic	"is-IS"
String	Igbo	"ig-NG"
String	Indonesian	"id-ID"
String	Inuktitut	"iu-CA"
String	Italian	"it-IT"
String	Italian_Switzerland	"it-CH"
String	Japanese	"ja-JP"
String	Kannada	"kn-IN"
String	Kanuri	"kr-TD"
String	Kashmiri	"ks-IN"
String	Kazakh	"kk-KZ"
String	Khmer	"km-KH"
String	Konkani	"kok-IN"
String	Korean	"ko-KR"

Type	Language Identifier	Language Code
String	Kyrgyz	"ky-KZ"
String	Lao	"lo-LA"
String	Latin	"la-XL"
String	Latvian	"lv-LV"
String	Lithuanian	"lt-LT"
String	Malay	"ms-MY"
String	Malay_Brunei_Darussalam	"ms-BN"
String	Malayalam	"ml-IN"
String	Maltese	"mt-MT"
String	Maori	"mi-NZ"
String	Marathi	"mr-IN"
String	Mongolian	"mn-MN"
String	Nepali	"ne-NP"
String	Nepali_India	"ne-IN"
String	Norwegian	"nb-NO"
String	Norwegian_Nynorsk	"nn-NO"
String	Oriya	"or-IN"
String	Oromo	"om-ET"
String	Panjabi	"pa-PK"
String	Polish	"pl-PL"
String	Portuguese	"pt-PT"
String	Portuguese_Brazil	"pt-BR"
String	Punjabi_Pakistan	"pa-PK"

Type	Language Identifier	Language Code
String	Pushto	"ps-AF"
String	Quechua_Ecuador	"qu-EC"
String	Quechua_Peru	"qu-PE"
String	Rhaeto_Romance	"rm-IT"
String	Romanian	"ro-RO"
String	Romanian_Moldova	"ro-MD"
String	Russian	"ru-RU"
String	Russian_Moldava	"ru-MD"
String	Sami	"se-NO"
String	Sanskrit	"sa-IN"
String	Serbian_Cyrillic	"sr-RS"
String	Serbian_Latin	"sr-SP"
String	Sindhi_India	"sd-IN"
String	Sindhi_Pakistan	"sd-PK"
String	Sinhala	"si-LK"
String	Slovak	"sk-SK"
String	Slovenian	"sl-SI"
String	Somali	"so-ET"
String	Sorbian	"wen-DE"
String	Spanish	"es-ES"
String	Spanish_Argentina	"es-AR"
String	Spanish_Bolivia	"es-BO"
String	Spanish_Chile	"es-CL"

Type	Language Identifier	Language Code
String	Spanish_Colombia	"es-CO"
String	Spanish_Costa_Rica	"es-CR"
String	Spanish_Dominican_Republic	"es-DO"
String	Spanish_Ecuador	"es-EC"
String	Spanish_El_Salvador	"es-SV"
String	Spanish_Honduras	"es-HN"
String	Spanish_LatinAmerica	"es-XL"
String	Spanish_Mexico	"es-MX"
String	Spanish_Nicaragua	"es-NI"
String	Spanish_Panama	"es-PA"
String	Spanish_Paraguay	"es-PY"
String	Spanish_Peru	"es-PE"
String	Spanish_Puerto_Rico	"es-PR"
String	Spanish_Uruguay	"es-UY"
String	Spanish_US	"es-US"
String	Spanish_Venezuela	"es-VE"
String	Swahili	"sw-TZ"
String	Swedish	"sv-SE"
String	Swedish_Finland	"sv-FI"
String	Syriac	"syr-SY"
String	Tajik	"tg-TJ"
String	Tamil	"ta-IN"
String	Tatar	"tt-RU"

Type	Language Identifier	Language Code
String	Telugu	"te-IN"
String	Thai	"th-TH"
String	Tibetan	"bo-CN"
String	Tigrinya_Eritrea	"ti-ER"
String	Tigrinya_Ethiopia	"ti-ET"
String	Tsonga	"ts-ZA"
String	Tswana	"tn-BW"
String	Turkish	"tr-TR"
String	Turkmen	"tk-TM"
String	Uighur	"ug-CN"
String	Ukrainian	"uk-UA"
String	Urdu	"ur-PK"
String	Urdu_India	"ur-IN"
String	Uzbek	"uz-UZ"
String	Venda	"ve-ZA"
String	Vietnamese	"vi-VN"
String	Welsh	"cy-GB"
String	Xhosa	"xh-ZA"
String	Yi	"ii-CN"
String	Yiddish	"yi-MD"
String	Yoruba	"yo-NG"
String	Zulu	"zu-ZA"

9 Appendix: Eloqua Language Codes

For instructions on mapping Eloqua language codes to Clay Tablet languages, see "[Configuring Clay Tablet Languages](#)".

Eloqua has the following language codes:

Language Identifier	Language Code
Afrikaans (South Africa)	af-ZA
Albanian (Albania)	sq-AL
Alsatian (France)	gsw-FR
Amharic (Ethiopia)	am-ET
Arabic (Algeria)	ar-DZ
Arabic (Bahrain)	ar-BH
Arabic (Egypt)	ar-EG
Arabic (Iraq)	ar-IQ
Arabic (Jordan)	ar-JO
Arabic (Kuwait)	ar-KW
Arabic (Lebanon)	ar-LB
Arabic (Libya)	ar-LY
Arabic (Morocco)	ar-MA
Arabic (Oman)	ar-OM
Arabic (Qatar)	ar-QA
Arabic (Saudi Arabia)	ar-SA
Arabic (Syria)	ar-SY
Arabic (Tunisia)	ar-TN
Arabic (U.A.E.)	ar-AE
Arabic (Yemen)	ar-YE

Language Identifier	Language Code
Armenian (Armenia)	hy-AM
Assamese (India)	as-IN
Azeri (Cyrillic, Azerbaijan)	az-Cyrl-AZ
Azeri (Latin, Azerbaijan)	az-Latn-AZ
Bashkir (Russia)	ba-RU
Basque (Basque)	eu-ES
Belarusian (Belarus)	be-BY
Bengali (Bangladesh)	bn-BD
Bengali (India)	bn-IN
Bosnian (Cyrillic, Bosnia and Herzegovina)	bs-Cyrl-BA
Bosnian (Latin, Bosnia and Herzegovina)	bs-Latn-BA
Breton (France)	br-FR
Bulgarian (Bulgaria)	bg-BG
Catalan (Catalan)	ca-ES
Chinese (Simplified, P.R.China)	zh-CN
Chinese (Simplified, Singapore)	zh-SG
Chinese (Traditional, Hong Kong S.A.R.)	zh-HK
Chinese (Traditional, Macao S.A.R.)	zh-MO
Chinese (Traditional, Taiwan)	zh-TW
Corsican (France)	co-FR
Croatian (Croatia)	hr-HR
Croatian (Latin, Bosnia and Herzegovina)	hr-BA
Czech (Czech Republic)	cs-CZ

Language Identifier	Language Code
Danish (Denmark)	da-DK
Dari (Afghanistan)	prs-AF
Divehi (Maldives)	dv-MV
Dutch (Belgium)	nl-BE
Dutch (Netherlands)	nl-NL
English (Australia)	en-AU
English (Belize)	en-BZ
English (Canada)	en-CA
English (India)	en-IN
English (Ireland)	en-IE
English (Jamaica)	en-JM
English (Malaysia)	en-MY
English (New Zealand)	en-NZ
English (Philippines)	en-PH
English (Singapore)	en-SG
English (South Africa)	en-ZA
English (Trinidad and Tobago)	en-TT
English (United Kingdom)	en-GB
English (United States)	en-US
English (Zimbabwe)	en-ZW
Estonian (Estonia)	et-EE
Faroese (Faroe Islands)	fo-FO
Filipino (Philippines)	fil-PH

Language Identifier	Language Code
Finnish (Finland)	fi-FI
French (Belgium)	fr-BE
French (Canada)	fr-CA
French (France)	fr-FR
French (Luxembourg)	fr-LU
French (Monaco)	fr-MC
French (Switzerland)	fr-CH
Frisian (Netherlands)	fy-NL
Galician (Galician)	gl-ES
Georgian (Georgia)	ka-GE
German (Austria)	de-AT
German (Germany)	de-DE
German (Liechtenstein)	de-LI
German (Luxembourg)	de-LU
German (Switzerland)	de-CH
Greek (Greece)	el-GR
Greenlandic (Greenland)	kl-GL
Gujarati (India)	gu-IN
Hausa (Latin, Nigeria)	ha-Latn-NG
Hebrew (Israel)	he-IL
Hindi (India)	hi-IN
Hungarian (Hungary)	hu-HU
Icelandic (Iceland)	is-IS

Language Identifier	Language Code
Igbo (Nigeria)	ig-NG
Indonesian (Indonesia)	id-ID
Inuktitut (Latin, Canada)	iu-Latn-CA
Inuktitut (Syllabics, Canada)	iu-Cans-CA
Irish (Ireland)	ga-IE
isiXhosa (South Africa)	xh-ZA
isiZulu (South Africa)	zu-ZA
Italian (Italy)	it-IT
Italian (Switzerland)	it-CH
Japanese (Japan)	ja-JP
K'iche (Guatemala)	qut-GT
Kannada (India)	kn-IN
Kazakh (Kazakhstan)	kk-KZ
Khmer (Cambodia)	km-KH
Kinyarwanda (Rwanda)	rw-RW
Kiswahili (Kenya)	sw-KE
Konkani (India)	kok-IN
Korean (Korea)	ko-KR
Kyrgyz (Kyrgyzstan)	ky-KG
Lao (Lao P.D.R.)	lo-LA
Latvian (Latvia)	lv-LV
Lithuanian (Lithuania)	lt-LT
Lower Sorbian (Germany)	dsb-DE

Language Identifier	Language Code
Luxembourgish (Luxembourg)	lb-LU
Macedonian (Former Yugoslav Republic of Macedonia)	mk-MK
Malay (Brunei Darussalam)	ms-BN
Malay (Malaysia)	ms-MY
Malayalam (India)	ml-IN
Maltese (Malta)	mt-MT
Maori (New Zealand)	mi-NZ
Mapudungun (Chile)	arn-CL
Marathi (India)	mr-IN
Mohawk (Mohawk)	moh-CA
Mongolian (Cyrillic, Mongolia)	mn-MN
Mongolian (Mongolian, P.R.China)	mn-Mong-CN
Nepali (Nepal)	ne-NP
Norwegian, Nynorsk (Norway)	nn-NO
Norwegian (Norway)	nb-NO
Occitan (France)	oc-FR
Oriya (India)	or-IN
Pashto (Afghanistan)	ps-AF
Persian (Iran)	fa-IR
Polish (Poland)	pl-PL
Portuguese (Brazil)	pt-BR
Portuguese (Portugal)	pt-PT
Punjabi (India)	pa-IN

Language Identifier	Language Code
Quechua (Bolivia)	quz-BO
Quechua (Peru)	quz-PE
Quechua (Peru)	es-PE
Quechua (Quechua)	quz-EC
Romanian (Romania)	ro-RO
Romansh (Switzerland)	rm-CH
Russian (Russia)	ru-RU
Sami, Inari (Finland)	smn-FI
Sami, Lule (Norway)	smj-NO
Sami, Lule (Sweden)	smj-SE
Sami, Northern (Finland)	sv-FI
Sami, Northern (Norway)	se-NO
Sami, Northern (Sweden)	se-SE
Sami, Skolt (Finland)	sms-FI
Sami, Southern (Norway)	sma-NO
Sami, Southern (Sweden)	sma-SE
Sanskrit (India)	sa-IN
Scottish (United Kingdom)	gd-GB
Serbian (Cyrillic, Bosnia and Herzegovina)	sr-Cyrl-BA
Serbian (Cyrillic, Montenegro)	sr-Cyrl-ME
Serbian (Cyrillic, Serbia)	sr-Cyrl-RS
Serbian (Latin, Bosnia and Herzegovina)	sr-Latn-BA
Serbian (Latin, Montenegro)	sr-Latn-ME

Language Identifier	Language Code
Serbian (Latin, Serbia)	sr-Latn-RS
Serbian (Latin, Serbia and Montenegro)	sr-Latn-CS
Sesotho sa Leboa (South Africa)	nso-ZA
Setswana (South Africa)	tn-ZA
Sinhala (Sri Lanka)	si-LK
Slovak (Slovakia)	sk-SK
Slovenian (Slovenia)	sl-SI
Spanish (Argentina)	es-AR
Spanish (Bolivarian Republic of Venezuela)	es-VE
Spanish (Bolivia)	es-BO
Spanish (Chile)	es-CL
Spanish (Colombia)	es-CO
Spanish (Costa Rica)	es-CR
Spanish (Dominican Republic)	es-DO
Spanish (Ecuador)	es-EC
Spanish (El Salvador)	es-SV
Spanish (Guatemala)	es-GT
Spanish (Honduras)	es-HN
Spanish (Nicaragua)	es-NI
Spanish (Panama)	es-PA
Spanish (Paraguay)	es-PY
Spanish (Puerto Rico)	es-PR
Spanish (Spain)	es-ES

Language Identifier	Language Code
Spanish (United States)	es-US
Spanish (Uruguay)	es-UY
Swedish (Finland)	sv-FI
Swedish (Sweden)	sv-SE
Syriac (Syria)	syr-SY
Tajik (Cyrillic, Tajikistan)	tg-Cyrl-TJ
Tamazight (Latin, Algeria)	tzm-Latn-DZ
Tamil (India)	ta-IN
Tatar (Russia)	tt-RU
Telugu (India)	te-IN
Thai (Thailand)	th-TH
Tibetan (P.R.China)	bo-CN
Turkish (Turkey)	tr-TR
Turkmen (Turkmenistan)	tk-TM
Ukrainian (Ukraine)	uk-UA
Upper Sorbian (Germany)	hsb-DE
Urdu (Islamic Republic of Pakistan)	ur-PK
Uyghur (P.R.China)	ug-CN
Uzbek (Cyrillic, Uzbekistan)	uz-Cyrl-UZ
Uzbek (Latin, Uzbekistan)	uz-Latn-UZ
Vietnamese (Vietnam)	vi-VN
Welsh (United Kingdom)	cy-GB
Wolof (Senegal)	wo-SN

9 Appendix: Eloqua Language Codes

Language Identifier	Language Code
Yakut (Russia)	sah-RU
Yi (P.R.China)	ii-CN
Yoruba (Nigeria)	yo-NG

Index

A

administrative tasks 57
App information, viewing 57
App usage data, viewing 57

C

Clay Tablet language codes 61
Clay Tablet languages, configuring 16
Clay Tablet Platform 7
Clay Tablet Support 9
Clay Tablet Translation Platform 7
CloudBroker, overview 15
configuration overview 16

D

Delete Team dialog box 47
Delete User dialog box 55
dynamic content, configuring translation settings 30

E

Edit Provider dialog box 36
Edit Site Team dialog box 44
Edit User dialog box 50
Eloqua authentication settings, viewing and testing 24
Eloqua dynamic content, configuring translation settings 30
Eloqua language codes 70

F

filename format, configuring 26

G

global translation settings, configuring 18
guide 8

I

Import Users dialog box 49
installation instructions 13
introduction 5

J

job data, viewing 59

L

language codes
 Clay Tablet 61
 Eloqua 70
Language Mapping dialog box 16
languages, configuring 16
Lionbridge Freeway authentication, configuring 20
location of target files, configuring 26
logging in 14

M

My Site page 57

N

New Provider dialog box 36
New Site Team dialog box 44
New User dialog box 52

O

overview
 CloudBroker 15

- pre-setup 12
- translation overview 7

P

- pre-setup overview 12

S

- SDL TMS entries, configuring 22
- Site Configuration dialog box
 - Eloqua tab, Access section 40
 - Eloqua tab, Authentication section 24
 - Options for LSP Freeway tab 20
 - Options for SDL TMS tab 22
 - Site Settings tab 18
 - Translation Settings tab 26
- Site Extension dialog box 30
- Site Jobs page 59
- Site Providers page 36
- Site Teams page 43
- Site Users page 48
- Statistics section, My Site page 57
- support 9

T

- target location, configuring 26
- teams
 - adding or editing 44
 - deleting 47
 - managing 43
- terminology 5
- translation providers, configuring 36
- translation settings
 - configuring 26
 - configuring for Eloqua dynamic content 30
- translation solution, overview 7

U

- user access, configuring 40

- users
 - adding 52
 - deleting 55
 - editing 50
 - importing 49
 - managing 48